

PU HOSE - HEAVY DUTY

Ether Grade

PU HOSE - K1Z - SSC - PU - VIRGIN FOOD GRADE



Structure:

Polyether - Polyurethane. Wall thick 1.2 mm

Characteristics:

Heavy and extremely flexible hose with good tensile and abrasion strengths and ultimate elongation, Free of softeners, halogens and cadmiums, resistant to hydrolysis and microbes

Applications:






Suction and conveying of abrasive particles and granules

Temperature range:

-40°C up to +100°C

Colour:

Transparent

 int mm	 mm	 mm	 bar	 VACUUM bar
32	1.2	38	3.0	0.70
35	1.2	42	3.0	0.70
38	1.2	46	3.0	0.70
40	1.2	48	3.0	0.70
42	1.2	50	3.0	0.70
45	1.2	54	3.0	0.70
48	1.2	58	3.0	0.70
50	1.2	60	3.0	0.70
51	1.2	61	2.5	0.60
55	1.2	66	2.5	0.60
60	1.2	72	2.5	0.60
65	1.2	78	2.5	0.60
70	1.2	84	2.5	0.60
75	1.2	90	2.5	0.60
76	1.2	91	2.5	0.60
80	1.2	96	2.0	0.50
83	1.2	100	2.0	0.50
90	1.2	108	2.0	0.50
100	1.2	120	2.0	0.50
102	1.2	122	1.5	0.42
110	1.2	132	1.5	0.42
120	1.2	144	1.5	0.42
125	1.2	150	1.5	0.42
127	1.2	152	1.5	0.42
130	1.2	156	1.5	0.42
140	1.2	168	1.5	0.42
150	1.2	180	1.5	0.42
152	1.2	182	1.5	0.42
160	1.2	192	1.0	0.33
175	1.2	210	1.0	0.33
180	1.2	216	1.0	0.33
200	1.2	240	1.0	0.33
203	1.2	244	1.0	0.33
225	1.2	270	1.0	0.33
250	1.2	300	0.7	0.25
280	1.2	336	0.7	0.25
300	1.2	360	0.7	0.25
350	1.2	420	0.7	0.25

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhosesbe@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018