

# PP AIR HOSE

**TEMP. 80°C**



## Structure:

Hose wall made of PP film and reinforced with extra strong spring steel wire. Capable of axial compression in to fixed position. A self supporting hose which can take any shape / position. Good resistance to UV and ozone, chemicals, fumes etc

## Applications:

Conveyance of air / dust, low temp. welding and soldering fume extraction, Chemical Fume exhaust, air conditioning and ventilation technology, printing / lamination machines and auto coner OHTC suction (Textile Machinery).

## Temperature range:

-20°C to +80°C






## Colour

Ivory

## Standard Length:

5 meter



				
int mm	out mm	mm	bar	bar
25	32	35	0.700	0.250
32	38	42	0.650	0.220
38	46	50	0.580	0.190
50	58	64	0.430	0.160
63	73	80	0.350	0.120
76	85	93	0.300	0.100
90	100	110	0.250	0.070
100	110	120	0.230	0.060
125	135	148	0.180	0.040
150	160	176	0.160	0.036
200	210	230	0.120	0.028
250	260	286	0.090	0.011

## Similar Products

### HDPE Semi Rigid Self Supporting Hose



Temp.:  
-20°C to +70°C  
Colour  
Black

### PVC Semi Rigid Duct Hose



Temp.:  
-10°C to +70°C  
Colour  
Grey / Black

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@be@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

**FLEXAFLEX HOSES INDUSTRIES**  
51, Dr. NANJAPPA ROAD  
COIMBATORE - 641 018