

# VACUUM LIFT HOSE



**Temp. : -7°C to 85°C**



## Structure:

Medium weight polypropylene elastomer hose (PPE) reinforced with both a plastic and spring steel wire helix.

Lifts most vacuum lift equipments.

Encapsulated high tension steel wire gives longer service life than traditional neoprene PVC wrapped construction.

Ideally suited for use in environments requiring frequent wash downs.

## Lift Capacity:

Single Tube – up to 300 lbs.

Dual Tubes – up to 650 lbs.

Triple Tubes – up to 1000 lbs.

## Applications:

Lifts most lift equipments

## Temperature range:

-7°C to 85°C

## Range :

Flexadux - Size mm (I.D.) : 127 mm to 200 mm ID

Jumboflex - Size mm (I.D.) : 100 | 120 | 140 | 150 | 160 | 180

## Colour:

Orange / Yellow / Red

## Standard Length :

10 Mtrs or OEM Length

## Specials :

Available with heat welded cuffs for easy air tight clamping

Also available in yellow colour and 8'.3" lengths

## Technical Data

I.D. mm	Weight kg/m	Wall. Thcik mm	Compression Ratio	Vacuum bar
4.72	0.90	0.24	03:01	13.0
5.00	0.90	0.3	03:01	18.5
6.30	1.30	0.3	03:01	16.3
7.09	1.70	0.3	03:01	14.0
7.87	2.00	0.3	03:01	13.0



Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@be@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

**FLEXAFLEX HOSES INDUSTRIES**  
51, Dr. NANJAPPA ROAD  
COIMBATORE - 641 018