

PVC SUCTION & DELIVERY FOOD GRADE HOSE FLEXANT

FOOD GRADE - PHTHALATE FREE - ANT



Structure :

Flexible Hose made of soft food grade PVC wall, in accordance with the modified EU regulation 10/ 2011, reinforced with shock resistant plastic spiral and copper wire on the outer surface for grounding

Wall Thick. : 3 to 6. 5 mm



Characteristics :

Smooth inside, Corrugated outside

Applications:







Designed for standard duty suction and delivery of liquids and low abrasion materials such as powder, pellets, wood chips and granules for plastic industries, vacuum pumps, liquids for food industries,

Temperature range:

0°C up to +60°C

Standard Packing :

25 Meters

|  |  |  |  |  |  |
|---|--|---|---|---|---|
| int mm | kg/m | mm | mm | bar | bar |
| 30 | 0.411 | 3.00 | 125.00 | 5.00 | 0.76 |
| 32 | 0.426 | 3.00 | 130.00 | 5.00 | 0.76 |
| 35 | 0.492 | 3.50 | 150.00 | 5.00 | 0.76 |
| 38 | 0.576 | 3.50 | 160.00 | 5.00 | 0.76 |
| 40 | 0.614 | 3.50 | 180.00 | 5.00 | 0.76 |
| 45 | 0.733 | 4.00 | 210.00 | 4.00 | 0.76 |
| 50 | 0.855 | 4.00 | 230.00 | 4.00 | 0.76 |
| 55 | 0.963 | 4.00 | 250.00 | 4.00 | 0.76 |
| 60 | 1.077 | 4.50 | 270.00 | 4.00 | 0.76 |
| 63 | 1.176 | 4.50 | 280.00 | 4.00 | 0.76 |
| 70 | 1.310 | 4.50 | 300.00 | 3.00 | 0.76 |
| 75 | 1.436 | 5.00 | 340.00 | 3.00 | 0.76 |
| 80 | 1.617 | 5.00 | 370.00 | 3.00 | 0.76 |
| 90 | 1.874 | 5.50 | 405.00 | 2.00 | 0.76 |
| 100 | 2.279 | 6.00 | 450.00 | 2.00 | 0.76 |
| 120 | 2.935 | 6.50 | 550.00 | 2.00 | 0.70 |



Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhosesce@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018