

SUPER STEAM HOSE DOUBLE WIRE BRAIDED

Temp. -40°C to +232°C



Structure:

- Inner Tube - EPDM Black
- Reinforcement - Single braid of high tensile brass coated steel wire for size 12.7 mm.
 - Two braids of high tensile brass coated steel wire for size 20.0mm to 50.0 mm.
- Cover - EPDM Black. Perforated

Applications:





Heavy duty industrial uses including heat control, melting of substances such as wax and glue, thawing, cleaning and steam transfer applications. It will handle all type of steam - saturated and superheated - up to 185 psi and + 232°C. Kindly avoid alternate change between steam and water

Temperature range:

-40°C to +232°C

Standards

Exceeds IS : 10655 Type 3 & B.S. : 5342 Type 2

|  |  |  |  |  |  |
|---|---|--|---|---|---|
| int mm | out mm | W.P. Kg/cm ² | B.P. Kg/cm ² | mm | in. Hg |
| 12.5 | 26.9 | 17.0 | 170.0 | 50.8 | 25.0 |
| 20.0 | 32.3 | 17.0 | 170.0 | 228.6 | 20.0 |
| 25.0 | 38.5 | 17.0 | 170.0 | 279.4 | 20.0 |
| 31.5 | 46.0 | 17.0 | 170.0 | 406.4 | 20.0 |
| 38.0 | 54.3 | 17.0 | 170.0 | 508.0 | 10.0 |
| 50.0 | 67.5 | 17.0 | 170.0 | 635.0 | 10.0 |

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@scbe@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018