

# CARBON FREE HOSE

**NON - Conductive Hose**



## Structure:

Inner Tube - Modified synthetic Rubber -  
Colour Grey

Reinforcement - High Tenacity synthetic yarn

Outer Cover - Special Nitrile Rubber Compound  
- Colour Green







## Applications:

Ideal for coolant applications in Induction furnaces and other non - conductive uses specially designed for low leakage current ( < 20 micro amp at 6KV DC )

## Temperature range:

-40° C to +100°C



					
int mm	out mm	W.P Kg/cm <sup>2</sup>	B.P. Kg/cm <sup>2</sup>	mm	in.Hg
12.7	21.6	17	69	101.6	25.0
19.8	31.0	17	69	127.0	25.0
26.2	37.5	17	69	152.4	25.0
32.4	45.2	17	69	190.5	25.0
39.2	53.6	17	69	203.2	20.0
51.8	66.0	14	56	304.0	10.0
63.5	81.0	14	56	508.0	10.0
76.2	93.5	14	56	635.0	5.0

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@be@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in | +91-94 897 38 415

**FLEXAFLEX HOSES INDUSTRIES**  
51, Dr. NANJAPPA ROAD  
COIMBATORE - 641 018