

# CEMENT GROUTING HOSE CONCRETE TRANSFER HOSE



## Structure:

- Inner Tube - special natural rubber
- Reinforcement - High tensile synthetic yarn twin copper wires ensure reliable conductivity
- Out Cover - Special Natural Rubber

## Applications:

For pumping concrete with high head pressure from concrete boom truck and as a discharge hose on the delivery end of high pressure concrete pumps. Ideal for handling wet concrete plaster or grout mixture.

## Temperature range:

-40°C to +70°C

int mm	out mm	W.P. Kg/cm <sup>2</sup>	B.P. Kg/cm <sup>2</sup>	mm	in. Hg
63.5	89	85	255	20.0	10.0
76.2	100	85	255	20.0	10.0

## CEMENT GROUTING HOSE / CONCRETE TRANSFER HOSE



int mm	out mm	W.P. bar	B.P. bar
25	31	10	30
31	38	10	30
38	48	10	30
50	62	10	30
63	75	10	30
75	89	10	30
100	116	10	30

Standard : Exceeds IS 5137 : 1990

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhosesce@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

**FLEXAFLEX HOSES INDUSTRIES**  
51, Dr. NANJAPPA ROAD  
COIMBATORE - 641 018