

STATIC CONDUCTIVE HOSE



Temp. -40°C to +100°C



Structure:

- Inner Tube - NBR (Nitrile)
- Reinforcement - One or two braid of high tensile synthetic yarn.
- Cover
 - Specially compounded highly abrasion resistant nitrile rubber for size 12.5 & 20.0 mm. Black
 - Highly abrasion resistant modified natural Rubber for size 25.0 mm. Black

Applications:

industrial applications like Oil, Alcohol, Aqueous solution, Hydraulic Fluid, Acids, Detergent and Chemical. Static conductive hose.

Temperature range:

-40°C to +100°C

int mm	out mm	W.P. Kg/cm ²	B.P. Kg/cm ²	mm	in. Hg
6.3	12.7	37	110	35	760.0
8.0	15.0	37	110	50	760.0
10.0	17.0	37	110	60	760.0
12.5	20.5	37	110	70	635.0
16.0	24.2	30	90	90	500.0
19.0	29.0	30	90	110	500.0
25.0	35.0	30	90	130	500.0
31.5	42.8	30	90	200	250.0
38.0	51.0	30	90	300	250.0
50.0	64.0	30	90	500	250.0

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@be@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018