

# HIGH TEMPERATURE CLIP HYPALON

Temp. - 40° C to + 175° C



## Structure:

Light weight and very flexible Hypalon® ducting

## Material:

Hypalon® coated polyester fabric / external: black, internal: green

## Properties

Good temperature, UV and ozone resistance, excellent chemical resistance, outer wear strip, flame retardant and excellent axial compressibility, good mechanical strength

## Application

Suction of hot or cold fumes, gases or dust in all fields of industry

## Temperature Resistance:







- 40° C to + 175° C

## Standard Length:

3 to 10 meters

## Special version:

Hypalon® T CL - 2-ply, internal: Teflon®-foil, external: Hypalon®-coated polyester tissue

 int mm	 kg/m	 mm	 mm	 bar	 bar
50	0.40	0.4	30	0.850	0.40
60	0.48	0.4	36	0.780	0.28
76	0.60	0.4	45	0.600	0.17
80	0.62	0.4	48	0.580	0.16
102	0.65	0.4	60	0.500	0.10
110	0.70	0.4	66	0.480	0.08
120	0.72	0.4	72	0.350	0.06
127	0.80	0.4	75	0.320	0.06
152	0.90	0.4	90	0.220	0.04
160	0.94	0.4	96	0.210	0.04
180	1.05	0.4	108	0.170	0.03
203	1.21	0.4	120	0.150	0.02
254	1.70	0.4	175	0.100	0.01
305	2.13	0.4	210	0.070	0.01
350	2.50	0.4	245	0.060	0.01
407	3.15	0.4	280	0.050	0.01
508	4.15	0.4	400	0.040	0.01