

HIGH TEMPERATURE CLIP PTFE

Temp. - 150° C to + 250° C



Structure:

Light weight and very flexible PTFE ducting

Material:

PTFE coated glass fabric, brown

Properties

Good temperature and chemical resistance, outer wear strip, good compressibility

Application

Suction of aggressive chemical fumes and gases in all fields of industry

Temperature Resistance:







- 150° C to + 250° C

Standard Length:

3 to 10 meters

Special construction:

PTFE® EL CL – conductive ($R < 10^6$ Ohm), conform to TRBS 2153 and ATEX guideline 94/9/EC, black

 int mm	 kg/m	 mm	 mm	 bar	 bar
50	0.40	0.12	30	0.850	0.32
60	0.50	0.12	36	0.680	0.22
76	0.60	0.12	45	0.470	0.14
80	0.63	0.12	48	0.430	0.12
102	0.65	0.12	60	0.300	0.08
110	0.70	0.12	66	0.250	0.07
120	0.72	0.12	72	0.220	0.06
127	0.80	0.12	75	0.210	0.05
152	0.90	0.12	90	0.160	0.04
160	0.94	0.12	96	0.140	0.03
180	1.05	0.12	108	0.120	0.02
203	1.21	0.12	120	0.100	0.02
254	1.70	0.12	175	0.070	0.01
305	2.13	0.12	210	0.050	0.01
350	2.30	0.12	245	0.040	0.01
407	2.90	0.12	280	0.030	0.01
508	3.90	0.12	400	0.020	0.01