

HIGH TEMPERATURE CLIP 450

Temp. - 60° C to + 450° C



Structure:

Very flexible ducting for temperatures up to + 450°C

Material:

2-ply, Inside: raw glass / Outside: high temperature silicone coated glass fabric, silver grey

Properties

Good temperature resistance, outer wear strip, flame retardant, excellent axial compressibility

Application







Suction of exhaust gases, flue gas extraction and suction of other hot fumes, gases or dust in all fields of industry

Temperature Resistance:

- 60° C to + 450° C

Standard Length:

3 to 10 meters
special lengths available.

 int mm	 kg/m	 mm	 mm	 bar	 bar
50	0.60	0.75	30	0.90	0.44
60	0.70	0.75	36	0.78	0.31
65	0.80	0.75	39	0.68	0.26
70	0.90	0.75	42	0.67	0.23
76	1.00	0.75	45	0.62	0.20
80	1.00	0.75	48	0.61	0.17
83	1.20	0.75	54	0.56	0.14
102	1.30	0.75	60	0.51	0.11
112	1.30	0.75	66	0.48	0.09
120	1.40	0.75	72	0.36	0.08
127	1.40	0.75	75	0.33	0.07
140	1.60	0.75	84	0.25	0.06
152	1.80	0.75	90	0.22	0.05
160	1.80	0.75	96	0.21	0.04
180	2.10	0.75	108	0.17	0.04
203	2.80	0.75	120	0.15	0.03
254	3.20	0.75	175	0.10	0.02
305	3.80	0.75	210	0.07	0.01
407	4.20	0.75	280	0.05	0.01
508	5.20	0.75	400	0.04	0.01