

NYLON (POLYAMIDE) CONDUIT PIPES AND GLANDS

Temp. : -10°C to +90°C



Structure:

Polyamide 6 - UL- 94 HB. Certified

Tensile Modules:

17300 Kg(f)cm²

Flexular Modules:

18400 Kg(f)cm²

Tensile Strength:

590 Kg/cm²

Impact Strength:

20 Kg/cm²

Applications:

Any machinery and industry, mechanical engineering, public utilities railway application, Vehicle construction, moving applications, building automation, robot-building, outdoor application (in black) in drag chains, many more in textile, plastic, printing, automotive compressor etc.

Temperature range:

-10°C to 90°C

Colour:

Black

(Other colors available on request)

Specials :

UV resistant conduits Slitted conduits

-Against - MOQ

I.D. mm	O.D. mm	Bending Radius	Standard Length / Mtr	Galnd Diameter	Assembly Threading
10.30	14.00	20	50	15	PG-9
10.80	15.80	30	50	18	PG-11
15.10	21.20	40	50	22	PG-16
19.80	28.50	42	50	29	PG-21
27.80	34.50	55	50	36	PG-29
35.00	42.50	62	25	45	PG-36
46.60	54.50	72	25	60	PG-48



Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhosesbe@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018