

# PVC FLAT DELIVERY HOSE



**Temp. : 0°C to +60°C**



## Structure:

Thick PVC coated synthetic woven fabric for better drag resistance on rough terrains keeping better working and bursting pressure.

## Pressure at 30°C

Working Pressure 2 to 4 kg/cm<sup>2</sup>






Bursting Pressure 3 to 12 kg/cm<sup>2</sup>

## Temperature range:

0°C to 60°C

## Applications:

Delivery hose for agriculture, construction sites, flood management, mines and quarries, marine and also for handling light chemical effluent.

 int mm	 mm	 W.P Kg/cm <sup>2</sup>	 B.P. Kg/cm <sup>2</sup>	 Std. Len. mtr
25	1.0	6.0	18	50/60/100
40	1.0	4.0	12	50/60/100
50	1.1	4.0	12	50/60/100
65	1.2	3.5	11	50/60/100
75	1.2	3.0	10.5	50/60/100
100	1.2	3.0	9	50/60/100
150	1.8	3.0	9	50/60/100
200	2.2	3.0	7.5	50/60/100
250	2.5	3.0	7	50/60/100
300	2.6	3.0	6	50/60/100

## Similar Products



### Agriculture Cotton Hose

Rubber lined cotton hose for agriculture purpose.

### Range:

1 1/2" to 4" ID

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@be@gmail.com | pipe.agencies@gmail.com

 [www.flexaflexhoses.in](http://www.flexaflexhoses.in) | [www.pipeagencies.in](http://www.pipeagencies.in)  +91-94 897 38 415

**FLEXAFLEX HOSES INDUSTRIES**  
51, Dr. NANJAPPA ROAD  
COIMBATORE - 641 018