

VACUUM LIFT HOSE



Temp. : -35°C to +135°C



Structure:

Wall made from Neoprene(CR) coated fiberglass fabric, reinforced with spring steel wire.

Characteristics:

Compressible hose : 3:1

Applications:

Specially designed for lifting heavy goods, as a component of vacuum lifting systems.

Temperature:
-35°C to 135°C

Colour:
Dark Blue

Wall Thickness :
0.7 - 1.2 mm

Standard Length :
500 mm to 4000 mm

Bending radius:
Same as Dia

Right rotation:
Yes



| I.D. mm | Wire. mm | Pitch. mm | KG Per Mtr. | Lift KG |
|---------|----------|-----------|-------------|---------|
| 80 | 1.4 | 12 | 0.81 | 20 |
| 102 | 1.55 | 12-13 | 1.02 | 30 |
| 120 | 1.8 | 12-14 | 1.20 | 40 |
| 140 | 2 | 11-14 | 1.35 | 50 |
| 160 | 2.25 | 11 | 1.80 | 60 |
| 178 | 2.5 | 11 | 2.12 | 80 |
| 203 | 2.5 | 11 | 2.73 | 100 |
| 229 | 3 | 11 | 3.26 | 120 |
| 250 | 3 | 11 | 3.56 | 160 |
| 305 | 3.5 | 11 | 3.80 | 270 |

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@scbe@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in | +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018