

PU HOSE - HEAVY DUTY

600 C - Ether Garde

Wall Thickness: 0.6 mm

Since 1990
FLEXAFLEX



Structure:

Wall made of abrasion resistant Polyurethane - as microbes and hydrolysis resistant version, (wall thickness between the spirals ca. 0,6mm), copper plated spring steel spiral embedded into wall

Characteristics:

Light and extremely flexible hose with good tensile and abrasion strengths and ultimate elongation. Free of softeners, halogen and cadmium free, ECO friendly.

Acc. to TRGS 727 and ATEX 2014/34 EU, with earthing at both ends of the spiral for nonflammable dusts and bulks solids in Zone 22. Gases and liquids with low conductivity of electrostatic charges in Zone 2

Temperature range:

-40°C to + 90°C (short-term up to + 125°C)

Colour:

Transparent,

Applications:

Universal hose for the woodworking, plastic and chemical industry for transportation of light solids and for air and gas transportation

Specials:

Compressed packaging available!

Also available as Flame Retardant Permantly Antistatic

 int mm	 Out mm	 mm	 mm	 kg/m app.	 mbar	 bar
32	36	0.6	32	0.164	350	0.7
35	39	0.6	35	0.179	350	0.7
★ 38	42	0.6	38	0.193	350	0.7
40	45	0.6	40	0.228	350	0.7
★ 42	47	0.6	42	0.239	350	0.7
★ 45	50	0.6	45	0.255	350	0.7
★ 48	53	0.6	48	0.271	350	0.7
★ 50	55	0.6	50	0.282	350	0.7
51	56	0.6	51	0.288	250	0.6
55	60	0.6	55	0.310	250	0.6

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018

PU HOSE - HEAVY DUTY

600 C - Ether Garde

Wall Thickness: 0.6 mm



						
int mm	Out mm	mm	mm	kg/m app.	mbar	bar
60	65	0.6	60	0.337	250	0.6
★ 65	70	0.6	65	0.364	250	0.6
70	75	0.6	70	0.432	250	0.6
★ 75	80	0.6	75	0.462	250	0.6
76	81	0.6	76	0.468	250	0.6
80	85	0.6	80	0.492	150	0.4
★ 83	88	0.6	83	0.510	150	0.4
90	95	0.6	90	0.552	150	0.4
★ 100	106	0.6	100	0.569	150	0.4
102	108	0.6	102	0.580	100	0.3
110	116	0.6	110	0.625	100	0.3
120	126	0.6	120	0.680	100	0.3
★ 125	131	0.6	125	0.708	100	0.3
127	133	0.6	127	0.720	100	0.3
130	136	0.6	130	0.736	100	0.3
140	146	0.6	140	0.792	100	0.3
150	156	0.6	150	0.848	100	0.3
152	158	0.6	152	0.859	100	0.3
160	166	0.6	160	0.903	50	0.2
175	181	0.6	175	0.987	50	0.2
180	186	0.6	180	1.015	50	0.2
★ 200	207	0.6	200	1.170	50	0.2
203	210	0.6	203	1.187	50	0.2
225	232	0.6	225	1.315	50	0.2
254	261	0.6	254	1.459	20	0.1
280	287	0.6	280	1.632	20	0.1
305	312	0.6	305	1.855	20	0.1
354	361	0.6	354	2.162	20	0.1

★ All These sizes are not in our ready stocks. Can be arranged on bulk orders.

● Further diameters upon Bulk order request.

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018