

ALUMINIUM COMBI HOSE

SEMI INSULATED ALUMINIUM FOIL HOSE



Structure:

COMBI is a high-quality flexible duct made from multi-layer aluminium and polyester, reinforced with high-tension steel spring wire, and finished with a durable PVC outer layer.

Key Features & Benefits:

● **Condensation Protection:** The PVC outer layer prevents moisture build-up, reducing the risk of mold growth and corrosion while maintaining indoor air quality.

● **Durability:** Enhanced resistance to punctures, tears, and mechanical stress.

● **Fire Resistance:** Suitable for HVAC and industrial environments where fire safety is critical.

● **Flexibility:** Easily installed on circular, oval, or rectangular connectors thanks to its elastic and flexible design.

Temperature range:

-30°C to +150°C

Std. Length:

10 Meters

Technical Properties

Types	Aluminium Combi	Inner Dia	Std Length
Construction	Aluminium+Polyester+PVC	52 mm	10 Mtr.
Temperature Range	-30°C to +150°C	63 mm	10 Mtr.
Air Velocity	30 m/s (max)	76 mm	10 Mtr.
Operating Pressure	3000 Pa (max)	102 mm	10 Mtr.
Standard Length	10 Meter	152 mm	10 Mtr.
		203 mm	10 Mtr.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018