

ALUMINIUM SEMI RIGID AIR DUCT

Temp. 150°C

Since 1990
FLEXAFLEX



Structure:



- ◆ Aluminium semi flexible air ducts are flexible, extendable and highly reliable for low and medium pressure air conditioning, ventilation, boiler systems and chimney liners.
- ◆ Hose is elastic, flexible and stretchable.
- ◆ Oval and circular connectors are easily installed.
- ◆ Hose is made secured using an "INTERLOCK" crimp system. "INTERLOCK" crimp systems minimize separation of the duct when it is stretched or bent.

Temperature range:



-30°C to +150°C

PROPERTIES & ADVANTAGES PURE ALUMINIUM BODY

- ◆ Non-combustible
- ◆ Impermeable to UV rays
- ◆ High resistance to UV rays
- ◆ Resistant to chemicals

SEMI-FLEXIBLE & INTERLOCK CONSTRUCTION

- ◆ Easy to transport & store
- ◆ Quick and easy installation
- ◆ Inseparable
- ◆ Leak proof
- ◆ Airtight
- ◆ Energy efficient
- ◆ Low operation and maintenance cost

Technical Properties

Types
Construction
Fire Resistance
Construction
Available Diameters
Standard Length
Air Velocity
Operating Pressure
Compression Rate

Semi Rigid
Pure Aluminium
Non -Combustible
Air Velocity
50 mm - 250 mm
3 Meter
25 m/s (max)
2000 Pa (max)
1/3

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018