



Structure:

Inner Tube: Specially compounded natural rubber.

Reinforcement: Single braid of high tensile Steel wire.

Cover :

Option 1: Specially compounded highly abrasion resistant natural rubber, black.

Option 2: Highly abrasion resistant modified Nitrile rubber - yellow. All sizes with perforated cover. Yellow cover MSHA IC11C. Flame Resistant.

Temperature range:

-30°C to +82°C

Applications:

Heavy duty, high pressure use on industrial construction and pneumatic mining applications, requiring an extra heavy duty hose with an oil resistant tube and abrasion resistant cover.

 int. mm	 Out. mm	 W.bar	 B.bar	 mm	 in. Hg
20.0	28.3	34.5	138.0	152.0	25.0
25.0	36.6	34.5	138.0	201.0	25.0
32.0	44.2	34.5	138.0	254.0	25.0
38.0	50.5	34.5	138.0	304.0	15.0
50.0	63.5	34.5	138.0	355.0	15.0
63.0	79.7	34.5	138.0	762.0	10.0
75.0	93.3	34.5	138.0	914.0	10.0

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.