

CARBON FREE HOSE

Since 1990

FLEXAFLEX

NON - Conductive Hose



Structure:



Inner Tube: Specially No carbon compounded NBR - Off White

Reinforcement: One or Two Braids of High Tenacity yarn.

Cover: Abrasion and Weather resistance NBR - PVC Green

Temperature range:



-40°C to +100°C

Applications:



Ideal for coolant applications in Induction furnaces and other non - conductive uses specially designed for low leakage current (< 20 micro amp at 6KV DC)



 int. mm	 Out. mm	 W.bar	 B.bar	 mm
10.0	17.5	17.5	70.0	70.0
12.5	21.5	17.5	70.0	100.0
20.0	31.0	17.5	70.0	150.0
25.0	37.5	17.5	70.0	150.0
31.5	45.0	17.5	70.0	195.0
38.0	52.0	17.5	70.0	200.0
50.0	66.0	17.5	70.0	300.0

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018