

FDA - GRADE CHEMICAL HOSE

Since 1990

FLEXAFLEX

UHMWPE



Structure:

UHMWPE, White, Smooth, Food Quality & Abrasion Resistant. Complies FDA Standards.

Reinforcement/ Cover:

Synthetic Plies, Helix Wire Embedded for strength. Antistatic copper wire for grounding.

Quality:

Complying with FDA standards Free from Phthalates, Animal Derivatives, Adipates, Plasticizers & Bisphenol A.

Temperature range:

-25°C Cleaning Upto 130°C For Max 30 Min

Colour:

Outer Cover - Blue / Inner layer - White

Applications:

Multipurpose Suction & Delivery Hose designed for Acids, Bases, Ketons, Aldehyds, Esters, Aromatic & Aliphatic Hydrocarbons. Suitable for Animal or Vegetable Foodstuffs & Alcoholic Drinks.

						
int mm	Out mm	mm	mm	bar	bar	Std. Len. mtr
19	32	6.5	190	16	48	40
25	40	5.5	250	16	48	40
32	47	5.5	315	16	48	40
38	53	6.5	375	16	48	40
51	66	7.5	500	16	48	40
64	80	8	625	16	48	40
76	95	8	750	16	48	40
102	122	9	1000	16	48	40

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018