

HIGH TEMPERATURE - CLIP 650

Since 1990

FLEXAFLEX

Temp: -60°C up to 650°C



Structure:

Very flexible ducting for temperatures up to + 650°C

2-ply, Silicone- coated high temperature fabric, reinforced by woven in stainless steel wire, silver-grey

Properties:

Good temperature resistance, outer wear strip, flame retardant, excellent axial compressibility

Temperature range:

-60°C up to 650°C

Colour:

Silver - Grey

Std. Length:

3 / 6 Meter

Applications:

Suction of exhaust gases, flue gas extraction and suction of other hot fumes, gases or dust in all fields of industry

 int. mm	 Out. mm	 mm	 mm	 bar
60	70.00	0.75	36	0.31
76	86.00	0.75	45	0.20
80	90.00	0.75	48	0.17
102	112.00	0.75	60	0.11
112	122.00	0.75	66	0.09
120	130.00	0.75	72	0.08
127	137.00	0.75	75	0.07
152	162.00	0.75	90	0.05
160	170.00	0.75	96	0.04
203	213.00	0.75	120	0.03
228	238.00	0.75	158	0.02
254	264.00	0.75	175	0.02
305	315.00	0.75	210	0.01
356	366.00	0.75	245	0.01
407	417.00	0.75	280	0.01
457	467.00	0.75	360	0.01
508	518.00	0.75	400	0.01

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.

● Further diameters upon Bulk order request

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018