

HIGH TEMPERATURE CLIP HOSE - HT-180

Since 1990

FLEXAFLEX

Temp: -65°C up to 180°C



Structure: ▼

Wall made of Single ply green Vinyl coated fibreglass fabric. It is mechanically crimped in a continuous process. Fabric is locked around a coated steel wire by a metal strip formed into a clip. Metal strip acts as a wearstrip and offers outstanding external abrasion resistance.

Characteristics: ▼

Tough and extremely flexible hose, Compressible, good resistance to high temperatures and chemicals.

Temperature range: ▼

-65°C up to 180°C

Colour: ▼

Green

Std. Length: ▼





10 Meter

Compression Ratio: ▼

5:1

Applications: ▼

Automotive, Brick Kilns, Cold Air Supply, Diesel/Engine Exhaust, Exhaust Systems, Flame Retardant, Foundries, Garage Exhaust, Heater, Jet Fuel Vapor Venting, Pollution Control, Vehicle Exhaust Systems.

 int. mm	 mm	 VACUUM psi	 psi
50	2.5	11	11.2
63	2.5	11	11.2
76	3.0	11	11.2
90	3.5	11	11.2
102	3.5	9	10
115	3.5	9	10
127	4.5	6	7
152	4.5	6	7
165	5.5	6	6
180	5.5	5	6
203	5.5	5	6
254	5.5	5	5
305	5.5	5	5

- All technical data are subject to dimensional tolerances of $\pm 0.5\%$.
- All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.
- Further diameters upon Bulk order request

+91-98 438 10 577

+91-94 897 38 415

+91-422 - 23 93 253

hoses@flexaflexhoses.in

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018