

HIGH TEMPERATURE CLIP HOSE - HT-450

Since 1990

FLEXAFLEX

Temp: -20°C up to 450°C



Structure: ▼

Wall made of Single ply silver Vinyl coated fibreglass fabric. It is mechanically crimped in a continuous process. Fabric is locked around a coated steel wire by a metal strip formed into a clip. Metal strip acts as a wearstrip and offers outstanding external abrasion resistance.

Temperature range: ▼

-20°C up to 450°C

Std. Length: ▼

10 Meter








Characteristics: ▼

Tough and extremely flexible hose, Compressible, good resistance to high temperatures and chemicals.

Applications: ▼

Automotive, Brick Kilns, Cold Air Supply, Diesel/Engine Exhaust, Exhaust Systems, Flame Retardant, Foundries, Garage Exhaust, Heater, Jet Fuel Vapor Venting, Pollution Control, Vehicle Exhaust Systems.



 Size - Inches	 int. mm	 mm	 mm	 psi	 psi	 compression ratio
2	50	0.45	3	10	16	3:1
2 1/2	63	0.45	3	10	16	3:1
3	76	0.45	3	10	16	3:1
3 1/2	89	0.45	3	10	16	3:1
4	102	0.45	3.5	9	15	3:1
4 1/2	115	0.45	3.5	9	15	3:1
5	125	0.45	5	9	15	5:1
6	150	0.45	7	7	15	5:1
8	200	0.45	6	7	12	6:1
10	250	0.45	5	6	10	8:1
12	300	0.45	5	4	10	8:1

- All technical data are subject to dimensional tolerances of $\pm 0.5\%$.
- All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.
- Further diameters upon Bulk order request

+91-98 438 10 577

+91-94 897 38 415

+91-422 - 23 93 253

hoses@flexaflexhoses.in

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018