


HIGH TEMPERATURE CLIP HYPALON

Since 1990

FLEXAFLEX

Temp: -40°C up to 175°C



Structure: ☐

Light weight and very flexible Hypalon® ducting

Material: ☐

2-ply, with PTFE foil inside
with stainless steel clip profile
with abrasion protection profile

Properties: ☐

Good temperature, UV and ozone resistance, excellent chemical resistance, outer wear strip, flame retardant and excellent axial compressibility, good mechanical strength

Temperature range: ☐

-40°C up to 175°C

Colour: ☐

External: Black,
Internal: Green

Std. Length: ☐

3 / 6 Meter

Applications: ☐

Suction of hot or cold fumes, gases or dust in all fields of industry

 int. mm	 Out. mm	 mm	 mm	 bar	 bar
50	60.00	0.40	30	0.40	0.85
60	70.00	0.40	36	0.28	0.78
76	86.00	0.40	45	0.17	0.60
80	90.00	0.40	48	0.16	0.58
102	112.00	0.40	60	0.10	0.50
112	122.00	0.40	66	0.08	0.40
120	130.00	0.40	72	0.06	0.35
127	137.00	0.40	75	0.06	0.32
140	150.00	0.40	83	0.04	0.25
152	162.00	0.40	90	0.04	0.22
160	170.00	0.40	96	0.04	0.21
180	190.00	0.40	108	0.03	0.17
203	213.00	0.40	120	0.02	0.15
228	238.00	0.40	135	0.01	0.12
254	264.00	0.40	175	0.01	0.10
305	315.00	0.40	210	0.01	0.07

 int. mm	 Out. mm	 mm	 mm	 bar	 bar
356	366.00	0.40	245	0.01	0.06
407	417.00	0.40	280	0.01	0.05
457	467.00	0.40	360	0.01	0.04
508	518.00	0.40	400	0.01	0.04

- All technical data are subject to dimensional tolerances of $\pm 0.5\%$.
- All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.
Max.operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.
- Further diameters upon Bulk order request