

HIGH TEMPERATURE CLIP PTFE

Since 1990

FLEXAFLEX

Temp: -150°C up to 250°C



Structure: ▼

Light weight and very flexible PTFE ducting PTFE coated glass fabric, brown

Properties: ▼

Good temperature and chemical resistance, outer wear strip, good compressibility

Temperature range: ▼

-150°C up to 250°C

Std. Length: ▼

3 / 6 Meter

Special construction: ▼

PTFE® EL CL – conductive ($R < 10^6$ Ohm), conform to TRBS 2153 and ATEX guideline 94/9/EC, black

Applications: ▼

Suction of aggressive chemical fumes and gases in all fields of industry

① int. mm	① Out. mm	↪ mm	R _q mm	VACUUM bar	① bar
50	60.00	0.12	30	0.32	0.85
60	70.00	0.12	36	0.22	0.68
76	86.00	0.12	45	0.14	0.47
80	90.00	0.12	48	0.12	0.43
102	112.00	0.12	60	0.08	0.30
112	122.00	0.12	66	0.07	0.25
120	130.00	0.12	72	0.06	0.22
127	137.00	0.12	75	0.05	0.21
140	150.00	0.12	83	0.04	0.25
152	162.00	0.12	90	0.04	0.16
160	170.00	0.12	96	0.03	0.14
180	190.00	0.12	108	0.02	0.12
203	213.00	0.12	120	0.02	0.10
228	238.00	0.12	135	0.01	0.12
254	264.00	0.12	175	0.01	0.07
305	315.00	0.12	210	0.01	0.05
356	366.00	0.12	245	0.01	0.04
407	417.00	0.12	280	0.01	0.03
457	467.00	0.12	360	0.01	0.04
508	518.00	0.12	400	0.01	0.04

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.
Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.

● Further diameters upon Bulk order request

☎ +91-98 438 10 577

☎ +91-94 897 38 415

☎ +91-422 - 23 93 253

✉ hoses@flexaflexhoses.in

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018