

Since 1990

FLEXAFLEX

HIGH TEMPERATURE CLIP SILICON

Temp: -60°C up to 300°C**Structure:**

Light weight and very flexible Silicone ducting
Silicone coated glass fabric, silver-grey

Properties:

Good temperature resistance, outer wear strip, flame retardant wall, excellent axial compressibility, good UV and ozone resistance, highly flexible.

Temperature range:**-60°C up to 300°C****Colour:****Silver - Grey****Std. Length:****3 / 6 Meter****Applications:**

Suction of hot fumes, gases or dust in all fields of industry

 int. mm	 Out. mm	 mm	 mm	 bar	 bar
50	60.00	0.40	30	0.32	0.85
60	70.00	0.40	36	0.22	0.68
76	86.00	0.40	45	0.14	0.47
80	90.00	0.40	48	0.13	0.43
102	112.00	0.40	60	0.08	0.30
112	122.00	0.40	65	0.07	0.25
120	130.00	0.40	72	0.06	0.22
127	137.00	0.40	75	0.05	0.21
140	150.00	0.40	83	0.04	0.18
152	162.00	0.40	90	0.04	0.16
160	170.00	0.40	96	0.03	0.14
180	190.00	0.40	108	0.02	0.12
203	213.00	0.40	120	0.02	0.10
228	238.00	0.40	135	0.01	0.09
254	264.00	0.40	175	0.01	0.07
305	315.00	0.40	210	0.01	0.05
356	366.00	0.40	245	0.01	0.04
407	417.00	0.40	280	0.01	0.03
457	467.00	0.40	360	0.01	0.02
508	518.00	0.40	400	0.01	0.02

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.

● Further diameters upon Bulk order request

 +91-98 438 10 577

 +91-94 897 38 415

 +91-422 - 23 93 253

 hoses@flexaflexhoses.in

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018