

NYLON (POLYAMIDE) CONDUIT PIPES AND GLANDS

Since 1990

FLEXAFLEX

Temp: -10°C up to 90°C



Structure: ▼

Polyamide PA6 - UL 94 V2. Certified

Properties: ▼

High fatigue life
High impact strength
Halogen free
Self-Extinguishing
High abrasion resistance
High UV resistance (Black)
Full-shrink packing

Colour: ▼

Black / Grey

Temperature range: ▼

-10°C up to 90°C

Applications: ▼

Any machinery and industry, mechanical engineering, public utilities railway application, Vehicle construction, moving applications, building automation, robot-building, outdoor application (in black) in drag chains, many more in textile, plastic, printing, automotive compressor etc.

Nominal Diameter mm	Inner Diameter mm	Outer Diameter mm	Standard Length meter	Gland Threading
7	6.5	10	100	PG 7
8.5	8.5	12	100	PG 7
9	10	13	100	PG 9
11	12	15.8	50	PG 11
13.5	14.5	18.4	50	PG 13.5
16	17	21.2	50	PG 16
19	19	24	50	PG 21
21	23.2	28.4	50	PG 21
26	26	31	50	PG 29
29	29	34.5	25	PG 29
36	36	42.5	25	PG 36
48	48	54.5	25	PG 48

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.



+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018