

PNEUMATIC TUBE AND ONE TOUCH FITTINGS

Since 1990

FLEXAFLEX

Blue / Transparent / Black / Yellow



PU Tubing



PU Tubing



PU Tubing - Spiral

Structure:

Polyurethane (PU) Tubing provides superior flexibility and minimal bending radius, ensuring reliable performance in tight and complex pneumatic installations.

Working Pressure:

6 to 10 kg/cm²

OD Tolerance :

±0.1mm

Colour :

Blue / Yellow / Black / Transparent

Applications:

Pneumatic tube and One touch fittings for all types of pneumatic cylinders - directional control valves, solenoid valves and other valves - Air preparation units like filter, regulator and lubricators - Pneumatic control panels - All compressed air lines, all machineries controlled by pneumatic systems - pneumatic circuits in any industry.

One Touch Fittings



PU Tubing

ID x OD mm	Working Pressure Kg/cm ²	Standard Length
2 X 4	10	100 Mtrs
2.5 X 4	10	100 Mtrs
3 X 5	10	100 Mtrs
4 X 6	8	100 Mtrs
5 X 8	12	100 Mtrs
5.5 X 8	10	100 Mtrs
6 X 8	8	100 Mtrs
6.5 X 10	10	100 Mtrs
8 X 10	5	100 Mtrs
8 X 11	7	100 Mtrs
8 X 12	10	100 Mtrs
9 X 12	8	100 Mtrs
10 X 12	6	100 Mtrs
10 X 14	8	100 Mtrs
12 X 16	6	100 Mtrs

PU Spiral

ID x OD mm	Working Pressure Kg/cm ²	Standard Length
4 X 6	8	3 / 5 / 10 / 15 Mtrs.
5 X 8	12	3 / 5 / 10 / 15 Mtrs.
5.5 X 8	10	3 / 5 / 10 / 15 Mtrs.
6.5 X 10	10	3 / 5 / 10 / 15 Mtrs.
8 X 12	10	3 / 5 / 10 / 15 Mtrs.
12 X 16	6	3 / 5 / 10 / 15 Mtrs.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018