

PVC BRAIDED HOSES - TRANSPARENT

(MEDIUM DUTY)



Structure: ▼

Medium duty hose made of oil and chemical resistant PVC, reinforced with non twisted nylon yarn which assure medium working pressure and temperature.

Range: ▼

6 mm ID to 50 mm ID

Color: ▼

Transparent

Temperature range: ▼

70°C

Applications: ▼

- ♦ Industrial Air Compressors - Air/Pneumatic Hoses.
- ♦ Steel Mills / Metal Casting Units.
- ♦ Cooling lines of induction Furnaces.
- ♦ Dyes and Chemical Handling.
- ♦ Bore Well Cleaning
- ♦ Suction and Delivery hose for Mine dewatering
- ♦ Water hose for Projects like Thermal Power Plants and other engineering Sites.
- ♦ Water hose for Plantations.
- ♦ Marine and ship building.
- ♦ Diesel and Edible oil handling.
- ♦ Plastic Raw Material handling.
- ♦ Vacuum Lines.

 Size - inch	 int mm	 Out mm	 bar	 Std. Len. mtr
1/4	6	12	20	100
5/16	8	13.5	20	100
3/8	10	15.5	18	100
1/2	12	18	16	100
5/8	15	22	12	100
3/4	20	26	12	50 / 100
1	25	31	10	50 / 100
1. 1/4	30	39	10	50 / 100
1. 1/2	40	46	9	30/50
2	50	60	8	30/50

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018