

PVC FLAT DELIVERY HOSE

TEMP: 0°C to +60°C

Since 1990
FLEXAFLEX



Structure: ▼

Thick PVC coated synthetic woven fabric for better drag resistance on rough terrains keeping better working and bursting pressure.

Colour: ▼

Blue

Temperature range: ▼

0°C to 60°C

Pressure at 30°C: ▼

Working Pressure 2kg/cm² to 4kg/cm²

Bursting Pressure 3kg/cm² to 12kg/cm²

Applications: ▼

Delivery hose for agriculture, construction sites, flood management, mines and quarries, marine and also for handling light chemical effluent.

 int mm	 mm	 W.P. Kg/cm ²	 B.P. Kg/cm ²	 Std. Len. mtr
25	1.0	4.0	12	50/60/100
40	1.0	4.0	12	50/60/100
50	1.1	3.0	9	50/60/100
65	1.2	3.0	7	50/60/100
75	1.2	3.0	7	50/60/100
100	1.2	3.0	7	50/60/100
150	1.8	3.0	6	50/60/100
200	2.3	2.0	4	50/60/100
250	2.5	2.0	3	50/60/100
300	2.7	2.0	3	50/100

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.



Similar Products

Agriculture Cotton Hose

Rubber lined cotton hose for agriculture purpose.

Range: 1 1/2" to 4" ID

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018