

PVC FLEXIBLE DUCT HOSE

Since 1990

FLEXAFLEX

GREY / TRANSPARENT / BLUE



Structure: ▼

Our duct hoses are manufactured with adequate reinforcement, achieved by embedding rigid thermoplastic spirals (such as hard PVC) within a soft PVC wall. This construction imparts both strength and flexibility to the hose.

The duct hose is a highly specialized product, widely used for conveying air, gases, light materials, and for dust handling applications. It is lightweight and flexible, making it easy to carry and convenient to use.

Temperature range: ▼

60°C / 70°C






Colour: ▼

Grey / Transparent / Blue








Applications: ▼

Well accepted hoses in Textile Machineries like OHTC (over head travelling cleaners), Carding and Drawing Machines, Comber, Blow Room, Auto Coner, Humidification Plants, Dust Collection Systems, Compact Spinning machines and also for various dust collection equipments with Spinning, Ginning, Twisting, Weaving, Dying, Cutting & Stitching and hosiery - Wood working industry - as dust collector hoses for Edge banders, CNC Routers and Engravers, Planners, Sanders, Panel saws - Warm air conveyance - fine dust and light non abrasive particle removal in asbestos and Fiberglass industries. Industrial vacuum cleaners and other floor care applications - material conveying in plastic processing machineries - rubber and chemical industries.


 Size - mm	 int mm	 Out mm	 bending radius mm	 Std. Len. mtr
22	21.00	28.60	35	30
25	25.40	32.10	45	30
30	31.80	38.60	50	30
40	38.00	45.00	55	30
50	50.80	57.20	65	30
60	60.00	67.00	70	30
65	63.50	71.50	75	30
75	76.20	83.50	95	30
80	81.20	88.00	100	30
90	91.40	98.00	115	30
100	101.20	108.90	125	30
110	111.80	118.00	130	30
125	127.00	135.20	140	15
140	142.20	149.00	180	15
150	152.40	161.10	205	15

PVC FLEXIBLE DUCT HOSE

 Size - mm	 int mm	 Out mm	 bending radius mm	 Std. Len. mtr
160	162.60	172.00	220	15
200	204.00	214.40	270	15
225	229.00	240.00	320	10
250	254.00	265.00	370	10
300	305.00	320.00	370	10

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.

 +91-98 438 10 577

 +91-422 - 2393 253 & 453

 flexaflexhoses@scbe@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018