

FLEXACIER STD FOOD

Food Grade - Phthalate Free

Since 1990
FLEXAFLEX



Structure: ▼

Flexible hose made out of soft phthalatefree food grade PVC wall in accordance with the modified EU regulation 10/2011 (simulants A, B, C, D1) and CE 1935/2004, reinforced with galvanized steel helix.

Properties: ▼

Smooth inside, smooth outside.

Std. Colour ▼

Transparent with galvanised steel spiral

Temperature range: ▼

-5°C to +65°C

Applications: ▼

Designed for standard duty suction and delivery of **high quality liquids and foodstuffs, including alcohol up to 50% in industry, agriculture, irrigation, water supply.**

Vacuum Lines of auto loaders in plastic processing industries like injection moulding blow moulding, extrusion for conveying resin and plastic granules, low temperature food grade material, powder and liquids in food processing and pharmaceutical industry, draining sewage and water. Used as oil drains for machineries and also other vacuum lines in different industries. Widely used for drinking water, edible oil, milk and other liquids in **food and pharma sectors.**

 int mm	 Out mm	 mm	 bar	 bar	 kg/m app.	 Std. Len. mtr
20	26.8	72	7.0	0.95	0.330	30
25	33.0	90	7.0	0.95	0.480	30
30	38.5	110	6.0	0.95	0.625	30
32	40.4	115	6.0	0.95	0.640	30
38	48.0	130	6.0	0.90	0.800	30
40	51.0	160	6.0	0.90	0.900	30
45	57.0	170	6.0	0.90	1.140	30
51	63.0	180	5.0	0.90	1.260	30
55	67.0	200	5.0	0.85	1.520	30
60	72.0	230	4.0	0.85	1.660	30
63	75.0	250	4.0	0.85	1.740	30
70	83.0	280	4.0	0.85	2.150	30
76	89.0	330	4.0	0.85	2.300	30
80	93.0	350	3.5	0.85	2.450	30

FLEXACIER STD FOOD

Food Grade - Phthalate Free

 int mm	 Out mm	 mm	 bar	 bar	 kg/m app.	 Std. Len. mtr
90	103	380	3.0	0.85	2.750	30
102	116	400	3.0	0.85	3.340	30
105	121	420	3.0	0.85	3.700	30
110	126	430	2.5	0.85	3.800	20
120	136	450	2.0	0.85	4.200	20
127	140	450	2.0	0.85	5.000	20
152	167	500	2.0	0.85	6.000	20

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.

 +91-98 438 10 577

 +91-422 - 2393 253 & 453

 flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018