



Structure: ▼

Inner Tube: NBR (Nitrile)

Reinforcement: One or two braids of high tensile synthetic yarn.

Cover : Specially compounded highly abrasion resistant nitrile rubber for size 12.5 & 20.0 mm. Black

Highly abrasion resistant modified natural Rubber for size 25.0 mm. Black

Temperature range: ▼

-45°C to +95°C app.

Applications: ▼

industrial applications like Oil, Alcohol, Aqueous solution, Hydraulic Fluid, Acids, Detergent and Chemical. Static conductive hose.

 int mm	 Out mm	 mm	 in.Hg	 W.Kg/cm ²	 B.Kg/cm ²
6.3	12.7	35	760.0	37	110
8.0	15.0	50	760.0	37	110
10.0	17.0	60	760.0	37	110
12.5	20.5	70	635.0	37	110
16.0	24.2	90	500.0	30	90
19.0	29.0	110	500.0	30	90
25.0	35.0	130	500.0	30	90
31.5	42.8	200	250.0	30	90
38.0	51.0	300	250.0	30	90
50.0	64.0	500	250.0	30	90

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.