

SUPER STEAM HOSE DOUBLE WIRE BRAIDED

Temp. -40°C to 232°C

Since 1990
FLEXAFLEX

Structure:

Inner Tube: EPDM Black

Reinforcement : Single braid of high tensile brass coated steel wire for size 12.7 mm.

Two braids of high tensile brass coated steel wire for size 20.0mm to 50.0 mm.

Cover: EPDM Black. Perforated

Temperature range:

-40°C to +232°C app.

Standards:

Exceeds IS : 10655 Type 3 & B.S. : 5342 Type 2

Applications:

Heavy duty industrial uses including heat control, melting of substances such as wax and glue, thawing, cleaning and steam transfer applications. It will handle all type of steam - saturated and superheated - up to 185 psi and + 232°C. Kindly avoid alternate change between steam and water

 int mm	 Out mm	 mm	 in.Hg	 W.Kg/cm ²	 B.Kg/cm ²
12.5	26.9	50.8	25.0	17.0	170.0
20.0	32.3	228.6	20.0	17.0	170.0
25.0	38.5	279.4	20.0	17.0	170.0
31.5	46.0	406.4	20.0	17.0	170.0
38.0	54.3	508.0	10.0	17.0	170.0
50.0	67.5	635.0	10.0	17.0	170.0

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018