

SAND BLAST / SHOT BLAST HOSE

SOLVENT HANDLINE HOSE



Structure:

Inner Tube: Highly Abrasion resistant, Synthetic Rubber -Black

Reinforcement: One or, Two Braided of high tenacity synthetic Yarn. Two Copper wire in opposite direction.

Cover: Abrasion Resistant, NR-SBR-Black.

Temperature range:

-30°C to +70°C (Continuous operation)

Applications:

short and sand blasting applications for cleaning metal surfaces, Casting, etching glass, where abrasive materials are conveyed at high velocity with electrical conductivity.

 int mm	 Out mm	 W.bar	 B.bar	 mm
20.0	39.0	10.0	30.0	200.0
25.0	45.0	10.0	30.0	300.0
31.5	53.0	10.0	30.0	400.0
38.0	59.0	10.0	30.0	450.0
50.0	73.0	10.0	30.0	500.0

SUPREME SANDBLAST

 int mm	 Out mm	 W.bar	 B.bar	 mm
20.0	33.5	14.0	56.0	175.0
25.0	39.5	14.0	56.0	225.0
31.5	48.5	14.0	56.0	250.0
38.0	55.0	14.0	56.0	300.0
50.0	67.5	14.0	56.0	400.0

- All technical data are subject to dimensional tolerances of $\pm 0.5\%$.
- All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018