

SLURRY SUCTION HOSE



Structure:



Inner Tube: Abrasion resistant natural rubber.

Reinforcement: High tensile synthetic plies with helix wire and copper wire for grounding.

Cover: Abrasion resistant natural rubber wrap finish.

Temperature range:



-40°C to +70°C

Applications:



Suction and discharge of bulk material like cement, gravel and sand etc in construction and slurry transportation in mining industry.

 int. mm	 Out. mm	 W.bar	 B.bar	 mm
31.0	44.0	10.0	30.0	190.0
38.0	51.0	10.0	30.0	230.0
50.0	64.0	10.0	30.0	310.0
63.0	78.0	10.0	30.0	380.0
75.0	91.0	10.0	30.0	460.0
100.0	119.0	10.0	30.0	610.0
125.0	146.0	10.0	30.0	760.0
150.0	173.0	10.0	30.0	920.0

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.

 +91-98 438 10 577

 +91-422 - 2393 253 & 453

 flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018