

STEAM HOSE

Since 1990

FLEXAFLEX

Temp. -40°C to +165°C



Structure: ▼

Inner Tube: EPDM Rubber Resistant to Saturated Steam

Reinforcement : High Tensile Textile Plies

Cover: Black, Smooth, Weather, Abrasion, Heat, Steam & Ozone Resistant Pin Pricked Special Synthetic Rubber. Fabric Impression

Temperature range: ▼





-40°C to +165°C App.

Standards: ▼

Exceeds IS : 5122: 1975 Type II

Applications: ▼

Suitable for general saturated steam service, including steam cleaning and sterilization applications

 int mm	 Out mm	 W.Kg/cm ²	 B.Kg/cm ²
13.0	25.0	7.0	70.0
19.0	33.0	7.0	70.0
25.0	38.0	7.0	70.0
32.0	44.0	7.0	70.0
38.0	50.0	7.0	70.0

- All technical data are subject to dimensional tolerances of $\pm 0.5\%$.
- All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018