

# VAT-ELASTIC HOSE VACUUM CLEANER HOSE

Since 1990

# FLEXAFLEX

## WET AND DRY FLOOR CARE



### Structure:

Highly flexible PVC hose reinforced with PVC coated spring steel wire and yarn embedded in to the outer PVC layer.

### Temperature range:

0°C to + 85°C







### Colour:

Black, other colours on request

**Also available with directly over moulded cuffs and connectors**


### Applications:

Multi-purpose hose for the transport of air, liquids and solid materials; especially designed for floor care devices, vacuum cleaners and automatic scrubbers.

 int mm	 Out mm	 mm	 mm	 mbar	 bar
25	31	0.5	31	400	1.7
27	34	0.5	34	350	1.6
32	38	0.5	38	350	1.5
35	41	0.5	41	300	1.4
38	44	0.5	44	300	1.4
41	47	0.5	47	300	1.4
44	50	0.5	50	280	1.3
51	57	0.5	57	280	1.3
60	66	0.5	66	250	1.3
63	69	0.5	69	250	1.0
70	76	0.5	76	200	0.9
76	82	0.5	82	180	0.8
80	86	0.5	86	180	0.7
89	95	0.5	95	170	0.7
102	108	0.5	108	150	0.6
110	118	0.5	118	150	0.6
114	123	0.5	123	120	0.6
127	133	0.5	133	110	0.6
150	158	0.5	158	110	0.5
160	168	0.5	168	100	0.5

● All technical data are subject to dimensional tolerances of ± 0.5%.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.

 +91-98 438 10 577

 +91-422 - 2393 253 & 453

 flexaflexhoses@gmail.com

[www.flexaflexhoses.in](http://www.flexaflexhoses.in)

**FLEXAFLEX HOSES INDUSTRIES**

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018