

# PP AIR HOSE

Since 1990

# FLEXAFLEX

Temp: 80°C



## Structure:

Hose wall made of PP film and reinforced with extra strong spring steel wire. Capable of axial compression in to fixed position. A self supporting hose which can take any shape / position. Good resistance to UV and ozone, chemicals, fumes etc

## Colour:





Ivory

## Temperature range:

-20 °C approx. to +80 °C approx.

## Applications:

Conveyance of air / dust, low temp. welding and soldering fume extraction, Chemical Fume exhaust, air conditioning and ventilation technology, printing / lamination machines and auto coner OHTC suction (Textile Machinery).

 int mm	 Out mm	 mm	 bar	 bar	 Std. Len. mtr
25	32	35	0.250	0.700	5.0
32	38	42	0.220	0.650	5.0
38	46	50	0.190	0.580	5.0
51	59	64	0.160	0.430	5.0
63	73	80	0.120	0.350	5.0
76	75	93	0.100	0.300	5.0
90	100	110	0.070	0.250	5.0
102	112	120	0.060	0.230	5.0
127	137	148	0.040	0.180	5.0
152	162	176	0.036	0.160	5.0
203	213	230	0.028	0.120	5.0
254	264	286	0.011	0.090	5.0

● All technical data are subject to dimensional tolerances of  $\pm 0.5\%$ .

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max.operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.

## Similar Products



PVC Semi Rigid Duct Hose

Temp.: -10°C to +70°C

Colour : Grey / Black

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

[www.flexaflexhoses.in](http://www.flexaflexhoses.in)

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018