WATER SUCTION & DISCHARGE HOSE

Since 1990

FLEXAFLEX



Structure:

Inner Tube: Specially Compounded Synthetic Rubber, Black

Reinforcement: High Strength Synthetic Plies With Helix Wire

Cover: Black Synthetic Rubber Cover

Temperature range:

-40°C to +70°C

Applications:

For suction and discharge of water and non-corrosive fluids, including wastewater and sewerage applications.

int. mm	Out. mm	W.bar	B.bar	mm
38.0	51.0	10.0	30.0	230.0
50.0	64.0	10.0	30.0	310.0
63.0	78.0	10.0	30.0	380.0
75.0	91.0	10.0	30.0	460.0
100.0	119.0	10.0	30.0	610.0
125.0	146.0	10.0	30.0	760.0
150.0	173.0	10.0	30.0	920.0

- All technical data are subject to dimensional tolerances of ± 0.5%.
- All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.
  Max. operating pressures apply only for short periods.
  We reserve the right to make technical changes and color deviations.
  Other versions are available upon request.

+91-98 438 10 577
+91-422 - 2393 253 & 453
flexaflexhosescbe@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD COIMBATORE - 641 018