

XLPE CHEMICAL HOSE

SOLVENT HANDLINE HOSE



Structure:

Inner Tube: White colour, Synthetic rubber with XLPE liner

Reinforcement: Plies of synthetic textile cords with steel helix and two cross anti static copper wires

Cover: Green colour EPDM, wrapped type, abrasion and weather resistant

Temperature range:

-20°C to +120°C (Continuous)

Applications:

Handling solvents like, toluene, xylene and other corrosive chemicals. Good resistance to Oils, Solvents and chemicals.

 int mm	 Out mm	 W.bar	 B.bar	 bar
19	30	17	51	0.9
25	35	17	51	0.9
32	44	17	51	0.9
38	50	17	51	0.9
51	67	17	51	0.9
63	79	17	51	0.9
76	94	17	51	0.9
102	120	17	51	0.9

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max. operating pressures apply only for short periods.

We reserve the right to make technical changes and color deviations.

Other versions are available upon request.

+91-98 438 10 577

+91-422 - 2393 253 & 453

flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018