

VENTILATION AIR DUCT HOSE (HVAC)

PVC Coated Polyester Fabric Hose

Temp. -20°C to +70°C

Since 1990
FLEXAFLEX



Structure:

Single ply yellow colour PVC coated polyester fabric hose with very strong spring steel wire reinforcement and black PVC profile wearstrip.

Features:

- ★ Light Weight Duct for Blower Applications
- ★ Compressibility ratio 11: 1
- ★ Compressibility allows for easy storage and transport
- ★ Resistant to UV Rays, Ozone
- ★ Water proof due to non porous fabric
- ★ Black wearstrip protects the hose against dragging
- ★ Fire Retardant
- ★ Can be supplied in antistatic version also
- ★ You may contact for extra sizes

Wall Thick:

0.5 mm

Colour:

Yellow

Temp:

-20°C to 70°C

Range:

102 mm to 609 mm ID

Standard Length:

10 / 15 Meters

Applications:

- ★ A/C Ventilations
- ★ Chiller
- ★ Dehumidification
- ★ Event Tent HVAC
- ★ Humidity Control
- ★ HVAC
- ★ Laser Engraving
- ★ Mining
- ★ Smoke Ejectors
- ★ Utility Blowers

Buckle Connection



String Connection



Hose ID mm	Steel wire Thickness mm	Pitch in Normal cm
102	1.8	16
115	1.8	16
127	1.8	16
152	1.8	16

VENTILATION AIR DUCT HOSE (HVAC)

PVC Coated Polyester Fabric Hose

Hose ID mm	Steel wire Thickness mm	Pitch in Normal cm
177	1.8	16
200	1.8	16
228	1.8	16
254	1.8	16
279	2.0	18
305	2.0	18
330	2.0	18
355	2.0	18
381	2.0	18
406	2.0	18
457	2.0	18
508	2.4	20
558	2.4	20
609	2.4	20
650	3.0	20
700	3.0	20
750	3.0	20
800	3.0	20 - 22
850	3.0	20 - 22
900	3.0	20 - 22
950	3.0	20 - 22
1000	3.0	20 - 22

● All technical data are subject to dimensional tolerances of $\pm 0.5\%$.

● All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances.

Max.operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations.

📞 +91-98 438 10 577

📞 +91-422 - 2393 253 & 453

✉️ flexaflexhoses@gmail.com

www.flexaflexhoses.in

FLEXAFLEX HOSES INDUSTRIES

51, Dr. NANJAPPA ROAD COIMBATORE - 641 018